

Technical Data – Rhino-Grip Anti Skid Additive

(90.41) E (G)

PRODUCT DESCRIPTION

PICS Rhino Grip is a finely ground and carefully graded micronised white powder which when added to PICS sealers will dramatically improve the Slip Resistance value of all concrete surfaces.

PURPOSE

PICS Rhino Grip is used to increase the Slip Resistance value on concrete surfaces. Typically used on inclined driveways, pathways, steps, patio's and swimming pool surrounds.

SPECIAL PROPERTIES

- Guaranteed increase in Slip Resistance value
- Effective Cost
- Careful grading ensures even distribution
- No dangerous sharp edges
- Transparent when applied
- Can be used on all re-seals

APPLICATION INSTRUCTIONS

Add the contents of the container to 25 lts of PICS **High Solids Sealer (CM41)** and mix well.

Ensure the **Rhino Grip** is evenly dispersed through the 25 lts of **High Solids Sealer (CM41)**.

Apply to the clean dry surface using a natural fibre brush.

Agitate every 20 minutes to avoid settlement.

For **Low Solids Sealer (CM42)** a second spray applied application (without **Rhino-Grip**) may be required depending on porosity of the surface.

For more detailed information please refer to the PICS Application Instruction Sheet.

01-02-2000

TECHNICAL & TEST DATA

| | |
|-------------------------------|------------------------|
| PACKAGE: | 0.5kgs Plastic Tub |
| YIELD: | 1 tub per 25 lts |
| STORAGE: | Indefinite |
| WATER SOLUBILITY: | Insoluble |
| XYLENE SOLUBILITY: | Insoluble |
| ODOUR: | None |
| BIOLOGICAL RESISTANCE: | Good/Non Biodegradable |

HEALTH AND SAFETY

PICS Rhino Grip is non toxic . Do not take internally. Avoid contact with eyes. Flush effected areas with water.

Refer to the Health & Safety Data Sheet for further information.

As this product is intended for use with either **High** or **Low Solids Sealer** please also consult the appropriate sealer Health & Safety Data Sheet.

TECHNICAL SERVICES

For further information, call our technical dept on:-
☎ UK (01635) 202224

☎ FAX (01635) 202230

☎ International +44(0) 1635 202224

☎ Fax International +44(0) 1635 202230

e-mail
Web Site

info@picsuk.com
www.picsuk.com